

ADMIRAL MERCHANTS MOTOR FREIGHT, INC.



General Offices:
 215 South 11th Street
 Minneapolis, MN 55403
 (612) 332-4819 • (800) 972-8864
 Fax: (612) 843-8182

Date:	<input type="checkbox"/> Tractor
	AMMF Unit #
	<input type="checkbox"/> Trailer
	AMMF Unit #
	<input type="checkbox"/> Flip Axle
	AMMF Unit #
VIN #:	<input type="checkbox"/> Other
	AMMF Unit #

FOR SELF INSPECTION USE ONLY

Components Inspected:		✓ Meets Standard	X Below Standard	
REQUIRED	1. Brake System			
	a. Service Brakes			
	b. Parking Brake Sytem			
	c. Brake Drums or Rotors			
	d. Brake Hose			
	e. Brake Tubing			
	f. Low Pressure Warning Device			
	g. Tractor Protection Valve			
	h. Air Compressor			
	i. Electric Brakes			
	j. Hydraulic Brakes			
	k. Vacuum System			
	REQUIRED	2. Coupling Devices		
		a. Fifth Wheels		
		b. Pintle Hooks		
c. Drawbar/Towbar Eye				
d. Drawbar/Towbar Tongue				
e. Safety Devices				
f. Saddle-Mounts				
	3. Exhaust System			
	4. Fuel System			
	5. Lighting System			
	6. Safe Loading			
	7. Steering Mechanism			
	a. Steering Wheel Free Play			
	b. Steering Column			
	c. Front Axle/All Steering Components			
	d. Steering Gear			
	e. Pitman Arm			
	f. Power Steering			
	g. Ball and Socket Joints			
	h. Tie Rods and Drag Links			
	i. Steering Linkage Nuts			
	j. Steering System			
	3. Suspension			
	a. Axle Positioning Parts			
	b. Spring Assembly			
	c. Torque/Radius/Tracking Components			
	9. Frame			
	a. Frame Members			
	b. Tire and Wheel Clearance			
	c. Adjustable Axle Assembly			
	d. Surface/Floor Condition			
	10. Tires (see below)			
	11. Wheels and Rims			
	a. Lock or Side Ring			
	b. Wheels and Rims			
	c. Fasteners			
	d. Welds			
	12. Windshield Glazing			
	13. Windshield Wipers			
	14. Safety Equipment			
	a. Fire Extinguisher			
	b. Triangles			
	15. Reflective Tape			
	Required on Tractors manufactured on or after July 1, 1997			

REQUIRED	RECORD COMPLETE INFORMATION	Tire & Brake Measurements				
	Pushrod travel for all positions in inch increments (ie: 2-1/2")	FRONT Push Rod Travel	RIGHT		RIGHT Push Rod Travel	
	Brake lining or pad thickness in 8th inch increments (ie: 2/8")		RF/32NDS LBS	RCO/32NDS LBS		RRO/32NDS LBS
	Tire Tread Depth for all positions in 32nds inch increments (ie: 4/32")		8THS	RCI/32NDS LBS		8THS
Tire Pressure for all positions	8THS		LCI/32NDS LBS	8THS		
		LF/32NDS LBS	LCO/32NDS LBS	LRO/32NDS LBS		
			LEFT			

FOR SELF INSPECTION USE ONLY

DRIVER NAME: _____ Printed Name Driver Signature _____ Signature Required